

PS26

Label Printing Scale

- Feature Rich Easy to Use Label Printing Scale.
- 10,000 PLU's, Easy to Setup and User Friendly.
- Ideal for Super Markets, Groceries and Specialty Stores.
- Affordable and delivers crisp and easy to read labels to all users.



Description

Easy to use these PS26 Weighing Scales are one of the most fast selling and popular label printing scales by Aflak. With 10, 000 PLU's these Label Printing Scales are easy to set up and are extremely user friendly. They deliver easy to read labels to all users having rich and colorful keyboard graphics. They are equipped with a 4 inch color TFT-LCD Double sided Display with a Pole. These Label Printing Scales are equipped with functions a retailer needs at an affordable price and are ideal for use in Super Markets, Groceries and Specialty Stores.

Features

- Print Parameters can be set and Barcode Formats can be accordingly customized.
- Big Storage Capacity: 10,000 PLU's inbuilt data storage capacity, with optional extra storage.
- Powerful Network Communication: Program Setting, Multiple Machine Networking, Back Office Management via ether RS-232 or Ethernet (TCP/IP).
- Supports ENGLISH / ARABIC Description on display and label print.
- Easy Programming: PLU's Database, Label Code Format, System Parameters, Hot Keys, 8 Letter Strings, 255 Explanation to be edited in PC or Directly in Scale
- Powerful Data Processing: 224 (112*2) PLU's Hot Key, Programmed and Printed in PC
- Supports Automatic Printing.
- User friendly Management software for easy upload of store PLU data to one or more Scales.

Specifications

ITEM	PARAMETERS
Precision	1/3000 F. S
Weighing scope	0-6Kg-15Kg or 0-15-30Kg
Weighing Resolution	2/5g or 5/10g
Storage Capacity	10,000 PLUs
Display	Green backlighting segment code LCD screens
	Peel: 6 figures
	- Weight: 6 figures
	- Unit price: 8 figures
Keyboard	- Total price: 8 figures
	140keys (112×2=224 PLU Hotkeys,
	28 Function keys)
Printing feature	Printing Method: thermal printing
	Resolution of level: 8dots/mm
	Printing speed: 60mm/s
	Printing life: ≥30km
Printing paper	Thermal printing label paper
	Label width: 30-60mm
	Label length: 25-48mm
	Paper roll internal diameter: ≤80mm
	Paper roll outer diameter: ≥42mm
	Interval space between labels: 2-3mm
Printing font	12×24 dot: 1.5mm(W) ×3.0mm(H)
Communication ports	1×RS232 Serial, 1×RJ45 Ethernet
Power supply	AC100-120V or AC200-240V, 50/60Hz
Power consumption	Normal status: 5W
	Printing status: 50W
Environmental Requirements	Storage temperature: -20°C ~ 50°C
	Working temperature: -10°C ~ 40°C
	Storage humidity: 10% ~ 95% RH
	Working humidity: 20% ~ 90% RH
Scale size (cm)	36(W)×44(D)×17.5(H) (the height is 49cm with display pole)
Package size (cm)	49(W)×48.5(D)×23(H)
Gross weight	About 9.3Kg

